



PRODUCT INFORMATION

QUAKER STATE HIGH PERFORMANCE MINERAL SAE 85W-140

QUAKER STATE HIGH PERFORMANCE MINERAL 85W-140 is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special Extreme Pressure additives.

QUAKER STATE HIGH PERFORMANCE MINERAL 85W-140 has especially been developed for the perfect lubrication of so-called "Limited Slip" and "Auto-Locking" hypoid transmissions.

- Excellent resistance against oxidation
- Very high activity against wear, corrosion and foam
- Low pour point
- Very good extreme pressure properties
- Excellent "Limited Slip" properties

TYPICAL PHYSICAL CHARACTERISTICS

SAE	85W-140
Density 15 °C	0,911 kg/l
Viscosity 40 °C	378,80 mm ² /s
Viscosity 100 °C	27,60 mm ² /s
Viscosity Index	99
Flash Point COC	245°C
Pour Point	-18°C

SPECIFICATIONS AND APPROVALS

API GL-5
MIL-L-2105D
ZF-TE-ML-05C, 12C

Feb 2006

Qomprador AB (publ), Karlavagnsgatan 11, SE-417 56 Göteborg, Sweden.
Telefon +46 31-51 35 20. Telefax +46 31-51 89 30. E-mail: quakerstate@qsab.se
Org. nr 556295-9741, VAT-No. SE556295974101

Qomprador AB (publ), Karlavagnsgatan 11, SE-417 56 Göteborg, Sweden.
Telefon +46 31-51 35 20. Telefax +46 31-51 89 30. E-mail: quakerstate@qsab.se
Org. nr 556295-9741, VAT-No. SE556295974101